



Representative Image

**Catalog No. TGN3322R****Description: 60A 3P GD N3R 240V NONFUSE SW****UPC No 783164008791****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > General Duty**

Designed for residential and light commercial applications where duty is not severe. Listed to UL standard 98 enclosed and dead front switches. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type GD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism (30-200 amp). 60/75 C conductor rating. TGN3322R

**Descriptors**

Category

General Duty

**Specifications**

Amperage 60 A

Poles 3

Wires 3

Fusing No Fuse

Enclosure NEMA 3R (Outdoor)

Wire Range (Cu/Al) 12-2

240 Vac, NEC Std, 1-ph 10.0 hp

240 Vac, NEC Std, 3-ph 15.0 hp

250 Vdc 10.0 hp

GSA Compliance Yes

**Classifications**

cUL Listed Yes

UL Listed Yes

**Dimensions**

Height 13.7 in

Depth 3.9 in

Width 8.4 in

Weight 10.0 lb

