



Representative Image

Catalog No. TH3362JCH**Description: 60A 3P HD N5/12 600V FUSIBLE RECPT****UPC No 783164126655****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed specifically for industrial welding applications. Incorporates Crouse Hinds interlocked receptacle (mating CH plugs sold separately). Listed to UL standard 98 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. Enclosure has no knockouts. TH3362JC

Descriptors

Category	Heavy Duty
GO Schedule	S1

Specifications

Voltage	600 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 5, 12 Drip/Dust-tight
Options	Crouse-Hinds Interlock
Wire Range (Cu/Al)	12-2
480 Vac, NEC Std, 1-ph	5
480 Vac, NEC Std, 3-ph	15
480 Vac, Time Delay, 1-ph	20
480 Vac, Time Delay, 3-ph	30
600 Vac, NEC Std, 1-ph	10
600 Vac, NEC Std, 3-ph	15
600 Vac, Time Delay, 1-ph	25
600 Vac, Time Delay, 3-ph	50
125 Vdc	5
250 Vdc	10
GSA Compliance	Yes

Classifications

cUL Listed	Yes
UL Listed	Yes

Dimensions

Height	19.3
--------	------

by ABB

Dimensions

Depth	5.7
Width	9.4
Weight	31