



### Catalog No. THN2262SSDC

Description: 60A 2P HD N4X SS 600VDC NONFUSE

UPC No 783164089592

Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

Designed specifically for 600Vdc motor applications. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. THN2262S



Representative Image

#### Descriptors

Category	Heavy Duty
GO Schedule	S1

#### Specifications

Voltage	600 DC
Amperage	60 A
Poles	2
Wires	2
Fusing	No Fuse
Enclosure	NEMA 4/4X Water/Dust-tight
Options	None
Wire Range (Cu/Al)	14-2
125 Vdc	5.0 hp
250 Vdc	10.0 hp
600 Vdc	25.0 hp
GSA Compliance	No

#### Classifications

cUL Listed	Yes
UL Listed	Yes

#### Dimensions

Height	19.3 in
Depth	5.7 in
Width	9.4 in
Weight	16.0 lb



