



Representative Image

**Catalog No. THN3362SS316****Description: 60A 3P HD N4X SS316 600V NONFUSE****UPC No 783164382365****Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

Designed for commercial and industrial applications where safety, high performance and continuity of service are essential. Listed to UL standard 98 enclosed and dead front switches. Suitable for use as service equipment when installed in accordance with the National Electrical Code. Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches. Meets or exceeds NEMA KS1 standard for enclosed switches, type HD. Fusible and non-fusible switches available (consult BuyLog for interrupt ratings). Quick-make, quick-break mechanism. 60/75 C conductor rating. Full cover interlocks. NEMA type 4X enclosure grade 316 stainless steel. THN3362S

**Descriptors**

Category	Heavy Duty
GO Schedule	S1

**Specifications**

Voltage	600 AC
Amperage	60 A
Poles	3
Wires	3
Fusing	No Fuse
Enclosure	NEMA 4/4X (316 Stainless)
Options	None
Wire Range (Cu/Al)	14-2
240 Vac, NEC Std, 3-ph	20
480 Vac, NEC Std, 1-ph	20
480 Vac, NEC Std, 3-ph	50
600 Vac, NEC Std, 1-ph	25
600 Vac, NEC Std, 3-ph	60
125 Vdc	5
250 Vdc	10
GSA Compliance	Yes

**Classifications**

cUL Listed	Yes
UL Listed	Yes

**Dimensions**

Height	13.3
Depth	5.2
Width	9.4

**by ABB**

## Dimensions

Weight

22