



Catalog No. TLM4222CCUG

Description: 225A 42CT 1P3W 22K IC FLD CONV WGRND BR

UPC No 783164158700

Home > Load Centers > Load Centers

PowerMark Gold convertible load centers arrive as main lug, but have the capability to have a main breaker installed. All ABB load centers are rated up to 60 degree/75 degree centigrade and is suitable for use with service entrance equipment when installed in accordance with electrical code. The TLM4222CCUG features space for 42, 1" breakers, 225 A bus ampere rating, a copper bus, a factory installed ground bar, and a combination/flush enclosure.

Descriptors

Category	Load Centers
Grouping	Single Phase - USA

Specifications

1" Space	42
1/2" Space	0
Amperage	225 A
Circuit Breaker Style	Plug-In
Device type	Main Lug
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	Yes
Feed	Either
Input/Output Voltage	120/240V ac
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	1 Phase

Classifications

UL/CUL Listing	UL
----------------	----

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers, meter combos, single socket metering, and residential circuit breakers Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.	DET1023	Application and Technical

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.