



Representative Image

Catalog No. TM42420C**Description: 200A 42CRT 3P4W 208Y/120V 10KIC CMB****UPC No 783164190045****Home > Load Centers > Load Centers**

Main breaker load centers arrive with a main breaker installed for a convenient and swift install. Main breakers allow for the user to stop the flow of electricity in the load center, shutting off all the power in the residence. The TM40420C features spaces for 40, 1" breakers, a 200A main ampere rating, 3 phases, and a combination surface/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	R7

Specifications

Load Center Type	Standard
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	22
Amperage	200 A
Device type	Main Breaker
Enclosure	Indoor
Phase	3 Phase
1" Space	42
1/2" Space	0
Feed	Top
Door	Yes
GSA Compliance	Yes
Circuit Breaker Style	Plug-In
NEMA Rating	NEMA 1
Factory Installed Ground Kit	No
# Branch Circuit 250A	42
Enclosure Type	Indoor, Combination
Wires	4 Wire
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac

Classifications

UL/CUL Listing	UL
----------------	----

Dimensions

Width	14.0 in
Depth	3.7 in

by ABB

Publications

Title	Publication No.	Publication Type
Section 1 BuyLog: Load centers and circuit breakers	DET1023	Application and Technical
Guide includes product features, photos, product number selection guide, knockout drawings, wiring diagrams, accessories and options list. Only available on-line.		

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.