



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

Search Parameters:

[e-Catalog](#) > [Load Centers](#) > Commercial/High-rise Residential

Load Centers,Commercial/High-rise Residential

Product #: TM42422C

Short Description: 225A 42CRT 3P4W 208Y/120V 10KIC CMB

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

Category	Three Phase
Input/Output Voltage	208Y/120V ac
Type	Standard
Interrupting Capacity Rating	22
Amperage	225A
Device Type	Main Breaker
Enclosure	Indoor Type 1 Enclosure, Combination
UL/CUL Listing	UL
Phase	3 Phase
1" Space	42
1/2" Space	20
Feed	Top
Door	Yes
GSA Compliance	No
GO Schedule	137
List Price	\$1597



[View Larger](#)

Publications/Resources

[TM42422C](#)

Additional Resources for Three Phase

[Drawings-Outline and Dimensional](#)
[Buy Log :1-16](#)

- UL Listed (Panelboards No. 67)
- 60°/75°C Conductor Rating
- Suitable for use as service entrance equipment when Installed in accordance with the National Electrical Code
- 22kAIC RMS symmetrical, Except Where Noted
- 6-42 circuit devices UL Listed for bottom mounted lugs by installing complete unit (box, interior and front) upside down
- For a listing of CSA Listed load centers, visit www.geelectrical.com



ORLWIDE PARTNER

[Home](#) | [Products](#) | [Services](#) | [Markets](#) | [Resources](#) | [Your Business](#) | [Where to Buy](#) | [Contact Us](#) | [EliteNet](#) | [Site Map](#) | [Mobile Website](#)
[Press Room](#) | [Corporate](#) | [Investor Information](#) | [Privacy Policy](#) | [Terms of Sale](#) | [Terms of Use](#)

Copyright General Electric Company 1997–