

Specification Sheet

Part Number: 2.5NFP0C



Sheathing allows flexible routing and lead-out of cables.

The inner edges are beveled preventing damage to cables.

Sheathing is reusable and resistant to most chemicals.

Spiralwrap is U.L. Recognized.

Spiralwrap Protective Sheathing, 0.38" Diameter, PE, Black, 100 ft/roll

Article Number 161-05024

Type 2.5NFP

Color Black (BK)

Quantity Per reel

Product Description HellermannTyton's Spiralwrap protective sheathing provides cable protection and flexible routing. Spiralwrap is wrapped around a group of cables to shield and organize.

Short Description Spiralwrap Protective Sheathing, 0.38" Diameter, PE, Black, 100 ft/roll

Global Part Name 2.5NFP-PE-BK

| | |
|--------------------------------|-------------------|
| Length L (Imperial) | 100.0 |
| Length L (Metric) | 30.48 |
| Variant | Spiral Binding |
| Bundle Diameter Min (Imperial) | 0.31 |
| Bundle Diameter Min (Metric) | 7.92 |
| Bundle Diameter Max (Imperial) | 3 |
| Bundle Diameter Max (Metric) | 76.2 |
| Diameter D (Imperial) | 0.375 |
| Diameter D (Metric) | 9.53 |
| Nominal Diameter (Imperial) | 0.38 |
| Nominal Diameter (Metric) | 9.53 |
| Wall Thickness WT (Imperial) | 0.052 |
| Wall Thickness WT (Metric) | 1.32 |
| Material | Polyethylene (PE) |
| Material Shortcut | PE |

| | |
|------------------------------|----------------------------------|
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -76°F to +190°F (-60°C to +88°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 100 |
| Package Quantity (Metric) | 30.48 |
| Customs Number | 3926909988 |

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)