# Specification Sheet

Part Number: CTP120STD

Split side is ideal for applications where braided tubing or spiral wrap may be difficult to install

Tubing provides full coverage where spiral wrap or other coverings may not be suitable

In harsh applications the tubing can provide resistance to crushing, impact, and abrasion

Tubing offers excellent protection against automotive fluids, vibration wear, water, snow, ice, and the effects of heat, cold, and sunlight on cables and wires

Convoluted Tubing, Slit, 0.5" Dia, PE, Black, 1100 ft/carton

| | |
|---|---|
| Article Number | 169-60507 |
| Type | CTP120 |
| Color | Black (BK) |
| Quantity Per | carton |

| | |
|---|---|
| Product Description | HellermannTyton’s Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer’s excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires. |
| Short Description | Convoluted Tubing, Slit, 0.5" Dia, PE, Black, 1100 ft/carton |
| Global Part Name | CTP120-PE-BK |
| Length L (Imperial) | 1100.0 |
| Length L (Metric) | 335.3 |
| Variant | Slit |
| Bundle Diameter Min (Imperial) | 0.1 |
| Bundle Diameter Min (Metric) | 1.0 |
| Bundle Diameter Max (Imperial) | 0.51 |
| Bundle Diameter Max (Metric) | 13.1 |
| Inner Diameter D (Imperial) | 0.516 |
| Inner Diameter D (Metric) | 13.11 |
| Diameter D (Imperial) | 0.70 |

| | |
|---|---|
| Diameter D (Metric) | 17.78 |
| Outside Diameter OD (Imperial) | 0.70 |
| Outside Diameter OD (Metric) | 17.78 |
| Nominal Diameter (Imperial) | 0.5 |
| Nominal Diameter (Metric) | 12.70 |
| Wall Thickness WT (Imperial) | 0.005 |
| Wall Thickness WT (Metric) | 0.127 |

| | |
|---|---|
| Material | Polyethylene (PE) |
| Material Shortcut | PE |
| Flammability | Not Flame Retardant |
| Halogen Free | No |
| UV Resistant (Yes/No) | No |
| Use Conditions | For Indoor Use Only |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| Reach Compliant (Article 33) | Yes |

| | |
|---|---|
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 1100 |
| Package Quantity (Metric) | 335.30 |
| Customs Number | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2026 HellermannTyton. All Rights Reserved.