

Pedestal, 2-Gang, Aluninum

By Hubbell Wiring Device-Kellems
Catalog # [FR80AL](#)

In-Floor Delivery Systems, Fire-Rated Poke-Throughs, Pedestal Series, Pedestal, 2-Gang, Aluninum

Features

- 1-4 hour fire rating (1-3 hour for steel floor units and concrete topping, D900 Series Design)
- For 2 1/4 in. to 7 in. floor thickness
- Approved for use in the City of Chicago

Performance

Electrical - Service Pedestal Construction - Heavy gauge aluminum frame with satin anodized aluminum housing with 302/304 stainless steel face plates

General

| | |
|------------------------------|---|
| Catalog Number | FR80AL |
| Color | Natural |
| EU RoHS Indicator | No |
| Finish Type | Aluminum |
| Item Type | Above Floor Service Fittings |
| Material | Aluminum |
| Material - Mounting Hardware | On PT7XC Through Floor Fitting |
| Mounting Hardware | Included |
| OEM Brand Name | Hubbell Wiring Device-Kellems |
| Specifications | <ul style="list-style-type: none">• Cubic Inch Capacity - 33.00 in. (540.9 cu cm³)• Pedestal Finish - Brushed |



• Power - 8.80 in. (144.2cm³)

• Voice/Data - 26.70 in. (437.6cm³)

Pedestals

783585396323

Dimensions

Display Size Standard Sized Product

Certifications And Compliance

Standards - RoHS Compliance CM
Status

Logistics

Carton Quantity 5

Product Assets

[Catalog Page - WDK P-35 Catalog Page](#)
[Catalog Page - WDK P-46 Catalog Page](#)
[Catalogs - WDK Catalog Full 2024](#)
[Installation Manuals - WIRING_PD1901_INSTALLINST](#)
[Sales Drawings - WDK_FR80AL_DRAWING_PDF](#)
[Specifications - FR80AL](#)
[Warranty - Industrial & Commercial Products](#)