



Features and Benefits

- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications



HBLI45123C20

Labor Savings are inREACH!



inREACH Industrial Cord Reels Connector Ends

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight lbs. (kg)	Catalog Number
White Industrial Reel.	with HBL5269CST	15	125	45 (13.7)	14/3 SJO	24.0 (10.9)
	with HBL5369CST with HBL2313	20	125	45 (13.7)	12/3 SJO	26.5 (12.0) 26.5 (12.0)
White Industrial Reel with Yellow Portable Outlet Box.	(1) 15A Duplex Receptacle (2) 15A Duplex Receptacles	15	125	45 (13.7)	14/3 SJO	26.5 (12.0) 26.5 (12.0)
	GFCI Module and (1) 15A Duplex Receptacle GFCI Module and (2) 15A Duplex Receptacles	15	125	45 (13.7)	14/3 SJO	26.5 (12.0) 26.5 (12.0)
White Industrial Reel with Black Portable Outlet Box.	(1) 15A Duplex Receptacle (2) 15A Duplex Receptacles	15	125	45 (13.7)	14/3 SJO	26.5 (12.0) 26.5 (12.0)
	GFCI Module and (2) 15A Duplex Receptacles	15	125	45 (13.7)	14/3 SJO	26.5 (12.0)
White Industrial Reel with Yellow Portable Outlet Box .	(1) 20A Duplex Receptacle (2) 20A Duplex Receptacles	20	125	45 (13.7)	12/3 SJO	26.5 (12.0) 26.5 (12.0)
	GFCI Module and (1) 20A Duplex Receptacle GFCI Module and (2) 20A Duplex Receptacles	20	125	45 (13.7)	12/3 SJO	26.5 (12.0) 26.5 (12.0)
White Industrial Reel with Black Portable Outlet Box.	(1) 20A Duplex Receptacle (2) 20A Duplex Receptacles	20	125	45 (13.7)	12/3 SJO	26.5 (12.0) 26.5 (12.0)
	GFCI Module and (2) 20A Duplex Receptacles	20	125	45 (13.7)	12/3 SJO	26.5 (12.0)
White Industrial Reel with Triple Tap .	GFCI Module and Triple Tap Outlet	15	125	45 (13.7)	12/3 SJO	26.5 (12.0)



HBLI45143C15



HBLI45123TL20



HBLI45143GF15



HBLI45143R15M1



HBLI45123R20



HBLI45123GF20

Note: 15A reels are supplied with HBL5266CST on the power supply cord. 20A reels are supplied with HBL5366CST on the power supply cord.
For shorter cable lengths, modify length indication in catalog number (i.e. HBLIXX); 25ft lengths are available.
For yellow reel, add 'Y' suffix to catalog number.
* For Kellems strain relief grip, add "K" suffix to catalog number.

inREACH Accessories

Description	Weight lbs. (kg)	Catalog Number
Mounting bracket.	2.5 (1.1)	HBLIMB
Mounting bracket with junction box mount.	3.0 (1.4)	HBLIMBJ
Mounting bracket.	3.5 (1.6)	HBLIACCMB*
Mounting bracket with junction box mount.	4.0 (1.8)	HBLIACCMBJ*
340° pivot base.	3.5 (1.1)	HBLI340PB
Replacement stop.	0.2 (.09)	HBLI16BS
		HBLI14BS
		HBLI12BS
		HBLI10BS



HBLIMB



HBLIMBJ



HBLI340PB



HBLI16BS



HBLI45123GF220M1



HBLI45123GFTT



HBLIPRBOX

Note: *Compatible with cord reel models from page K-4 marked with a single asterisk (*).

Plenum Rated Enclosure for inREACH Cord Reels

Description	Weight lbs. (kg)	Catalog Number
Plenum rated enclosure.	30 lbs. (13.6)	HBLIPRBOX

Note: Check with manufacturer for compatible cord reel models.

Dimensions in Inches (mm)