

Features and Benefits

- UL Type 4 environmental listing
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications



HBLW45143



inREACH Industrial Weatherproof Cord Reels

Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight lbs. (kg)	Yellow Reel	White Reel
10	600	45 (13.7)	16/3 SOW 16/4 SOW	23.6 (10.7) 25.6 (11.6)	HBLW45163 HBLW45164	HBLW45163W HBLW45164W
15	600	45 (13.7)	14/3 SOW 14/4 SOW	28.2 (12.8) 30.0 (13.6)	HBLW45143 HBLW45144	HBLW45143W HBLW45144W
18 16	600	80 (24.4) 75 (22.9)	12/3 SOW 12/4 SOW	97.5 (44.2) 107.4 (48.7)	— —	HBLW80123W* HBLW75124W*
20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	HBLW45123	HBLW45123W
		40 (12.2)	12/4 SOW	32.2 (14.6)	HBLW40124	HBLW40124W
		25 (7.6)	12/3 SOW	24.9 (11.3)	HBLW25123	HBLW25123W
25 20	600	75 (22.9) 75 (22.9)	10/3 SOW 10/4 SOW	103.8 (47.1) 116.2 (52.7)	— —	HBLW75103W* HBLW75104W*
30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	HBLW40103	HBLW40103W
		35 (10.7)	10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
		25 (7.6)	10/4 SOW	30.2 (13.7)	HBLW25104	HBLW25104W
40 30 35	600	45 (13.7) 60 (18.3) 45 (13.7)	8/3 SOW 8/3 SOW 8/4 SOW	106.5 (48.3) 123.2 (55.9) 122.8 (55.7)	— — —	HBLW4583W* HBLW6083W* HBLW4584W*
55 55	600	45 (13.7) 45 (13.7)	6/3 SOW 6/4 SOW	123.0 (55.8) 126.7 (57.5)	— —	HBLW4563W* HBLW4564W*
14 6	600	45 (13.7) 45 (13.7)	12/8 SOW 14/12 SOW	107.4 (48.7) 113.5 (51.5)	— —	HBLW45128W* HBLW451412W*



HBLW45123W



HBLW45143



HBLW40103

inREACH Accessories

Description	Weight lbs. (kg)	Catalog Number
Mounting bracket.	2.5 (1.1)	HBLIMB
Mounting bracket with junction box mount.	3.0 (1.4)	HBLIMBJ
Mounting bracket.	3.5 (1.6)	HBLIACCMB*
Mounting bracket with junction box mount.	4.0 (1.8)	HBLIACCMBJ*
340° pivot base.	3.5 (1.6)	HBLI340PB
Replacement stop.	0.2 (.09)	HBLI16BS HBLI14BS HBLI12BS HBLI10BS



HBLIMB



HBLIMBJ



HBLI340PB



HBLI10BS

Note: *Compatible with cord reel models marked with a single asterisk (*).

Dimensions in Inches (mm)