

Hubbell's newly redesigned inREACH Industrial and Industrial Weatherproof Cord Reels improve existing user safety and maximize efficiency by managing cord and power in a safe and organized manner, while also meeting the most demanding industrial environment needs for years with little to no maintenance.

inREACH Industrial and Industrial Weatherproof Cord Reels are listed to UL 355 and CSA, C22.2 No. 308 with a durable, lightweight low profile cast aluminum construction. inREACH Reels also feature a newly designed mounting plate that allows for a quick easy installation on any surface.



**inREACH** No matter what your need,  
Hubbell will always be inREACH!

**inREACH Industrial Cord Reels**

- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications

**inREACH Industrial Cord Reels**

Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight lbs. (kg)	Black Reel	White Reel	Yellow Reel
10	250	45 (13.7)	16/3 SJO	22.9 (10.4)	—	HBLI45163	HBLI45163Y
			16/4 SJO	23.6 (10.7)	—	HBLI45164	HBLI45164Y
15	250	45 (13.7)	14/3 SJO	24.0 (10.9)	—	HBLI45143	HBLI45143Y
			14/4 SJO	25.4 (11.5)	—	HBLI45144	HBLI45144Y
20	250	45 (13.7)	12/3 SJO	26.5 (12.0)	HBLI45123BLK	HBLI45123	HBLI45123Y
			12/3 SJO	26.5 (12.0)	—	HBLIWC45123**	—
			12/4 SJO	29.8 (13.5)	—	HBLI45124	HBLI45124Y
		25 (7.6)	12/3 SJO	23.4 (10.6)	—	HBLI25123	HBLI25123Y
			12/4 SJO	24.5 (11.1)	—	HBLI25124	—
18	250	70 (21.3)	12/3 SJO	79.6 (36.1)	—	HBLI70123*	—
18	250	90 (27.4)	12/3 SJO	86.5 (39.2)	—	HBLI90123*	—
16	250	80 (24.4)	12/4 SJO	85.1 (38.6)	—	HBLI80124*	—
30	250	45 (13.7)	10/3 SJO	32.4 (14.7)	—	HBLI45103	HBLI45103Y
		40 (12.2)	10/4 SJO	33.7 (15.3)	—	HBLI40104	HBLI40104Y
		25 (7.6)	10/3 SJO	26.0 (11.8)	—	HBLI25103	HBLI25103Y
25	250	80 (24.4)	10/3 SJO	104.3 (47.3)	—	HBLI80103*	—
25	250	80 (24.4)	10/4 SJO	113.3 (51.4)	—	HBLI80104*	—



HBLI45123



HBLI45123BLK



HBLI45103Y

Note: \*See page K-5 for compatible mounting brackets. / \*\*Supplied with White cable.

Dimensions in Inches (mm)