



**IP20**  
SUITABILITY



**Plugs**


| Description   | Cord Dia.                 | Catalog Number         |                        |                               |
|---|---------------------------|------------------------|------------------------|-------------------------------|
|   |                           | 15A 125V<br>NEMA ML-1P | 15A 125V<br>NEMA ML-2P | 15A 125/250V AC<br>NEMA ML-3P |
| Valise plug, black nylon, multiple drive screw terminals.                     | .220"-.385"<br>(5.6-9.8)  | HBL7465V*              | —                      | —                             |
| Valise plug, black nylon, insulation displacement terminals.                  | .300"-.430"<br>(7.6-10.9) | —                      | HBL7594V               | —                             |
| Black nylon cover, phenolic body, multiple drive screw terminals.             | .281"-.421"<br>(7.1-10.7) | —                      | HBL7594                | —                             |
| Angle plug, black nylon cover, phenolic body, multiple drive screw terminals. | .335"-.421"<br>(8.5-10.7) | —                      | HBL7570                | —                             |
| Valise plug, black nylon, with insulation displacement terminals.             | .300"-.430"<br>(7.6-10.9) | —                      | —                      | HBL7485V*                     |
| Black nylon body, phenolic base, multiple drive screw terminals, cord grip.   | .281"-.421"<br>(7.1-10.7) | —                      | —                      | HBL7485*                      |
| Same as above, except angle cord grip.  | .335"-.421"<br>(8.5-10.7) | —                      | —                      | HBL7432*                      |



**HBL7465V**



**HBL7594V**



**HBL7594**

**Flanged Inlets**


| Description   | Catalog Number |          |           |
|---|----------------|----------|-----------|
| Stainless steel flange, polarized, exposed terminals.                     | HBL7467*       | —        | —         |
| Stainless steel flange, not polarized, exposed terminals.                 | HBL7466*       | —        | —         |
| Exposed terminals, black nylon flange.                                    | —              | HBL7595N | —         |
| Exposed terminals, stainless steel flange.                                | —              | HBL7595  | —         |
| Covered terminals, stainless steel flange, accepts cord .500" (12.7) dia. | —              | HBL7551  | —         |
| Exposed terminals, black nylon flange.                                    | —              | —        | HBL7486N* |
| Exposed terminals, stainless steel flange.                                | —              | —        | HBL7486*  |

Note: See page C-8 for accessories.


\*UL Listed only.

Male ML-2P devices have hollow center ground sleeves.


Male ML-3P devices have solid center neutral pins.




**HBL7570**




**HBL7466, HBL7467**




**HBL7595**



**HBL7486N**



**HBL7486**



**HBL7595N**

Dimensions in Inches (mm)