

**For 15 and 20 Ampere, 125 and 250 Volts
and 277 Volts AC Devices**



**Weatherproof Covers
For Nylon Flanged Inlets and Flanged Receptacles**

IP44
SUITABILITY

Description	Catalog Number
RTP, gray, for FS/FD box mounting.	WP1

*Note: RTP is an abbreviation for reinforced thermoplastic polyester.
See page P-21 for additional information on weatherproof covers.*



WP1

Weatherproof Boots

IP55*
SUITABILITY

Description	Catalog Number
Seal-Tite® triple seal, black elastomer cover for Insulgrip® plugs (HBL5266C style), when used in a cord set, and connector bodies (HBL5269C style), when used with flanged inlets.	HBL6017
Same as above except yellow.	HBL60CM17
Seal-Tite® triple seal black elastomer cover for Insulgrip® connector bodies when used in a cord set.	HBL6018
Same as above except yellow.	HBL60CM18
Closure plug, black.	HBL6019
Closure plug, yellow.	HBL60CM19

*Note: *IP55 when installed and used properly with mating components.
Boots are not UL Listed or CSA Certified.*



HBL6017



HBL6018




HBL60CM19
Shown with HBL6018

PLUGOUT® Device

Description	Catalog Number
Electrical plug lockout devices for 15 and 20A straight blade plugs, yellow.	HLDMP
Electrical plug lockout device for 20 and 30A Hubbell plugs and others, yellow.	HLD
Yellow lockout kit, one each of HLDMP, HLD, HLD2, and HSLDPK2.	HLDKIT
Red keyed PLUGOUT, keyed differently, for 15 and 20A, 125V straight blade plugs with holes in blades.	HKLDR

See section L for additional information on lockout devices.



HLDMP



HLD

Inserts

Description	Catalog Number
Replacement cord grip inserts for Valise® device, (bag of 40).	HBLVCGBK

Receptacle Circuit Tester



Description	Catalog Number
Receptacle circuit tester.	HBL5200



HBL5200

Dimensions in Inches (mm)