

**Hubbell-PRO Heavy Duty, Straight Blade Hospital Grade Duplex Receptacles**



**Specifications**

Receptacles	Part	Description
Typical Specification - Catalog No. <b>8200</b>	Receptacle	15A
Manufacturer's Identification - Hubbell-PRO <b>8200</b>	Top	Polycarbonate
Description - Straight Blade Hospital Grade Duplex Receptacle	Base	RTP*
Type - 2 Pole, 3 Wire, Grounding	Triple Wipe Power Contacts	.032 not .0295
Rating - 15A, 125V	Clamping Plate	Plated Steel
Certification - UL Listed to UL 498, Fed. Spec. WC596	Mounting Strap	.050 in. Galvanized Steel
Hospital Grade, NEMA® WD-6 Compliant	Terminal Screws	Plated Steel
Certified to CSA	Hex Head Grounding Screw	Plated Steel
	Automatic Self-Grounding Staple	Stainless Steel
	Mounting Screws	Zinc Plated Steel

**Performance**

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL 498 and CSA (Brass, White, Green)
Terminal Accommodation	#14-10 AWG stranded or solid copper conductor only.
Product Identification	Ratings are a permanent part of the device.
Environmental – Material	
Flammability	UL 94V-2.
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact).

Note: \*Reinforced Thermoplastic Polyester.

NEMA is a registered trademark of the National Electrical Manufacturers Association.

Dimensions in Inches (mm)