

15 and 20 Ampere, 125 Volts



15A 250V
NEMA 6-15R
UL CSA
1.5 HP




20A 250V
NEMA 6-20R
UL CSA
2 HP




**HBL® Extra Heavy Duty Max
Specification Grade Receptacles**

Description	Color	Catalog Number	
Duplex			
Flush, nylon face, back and side wired, multiple drive screws.	Black	—	HBL5462BK
	Brown	HBL5662	HBL5462
	Gray	—	HBL5462GY
	Ivory	HBL5662I	HBL5462I
	Red	—	HBL5462R
Isolated ground ^Δ .	Orange	IG5662	IG5462
Single			
Flush, nylon face, back and side wired.	Brown	HBL5661	HBL5461
	Gray	—	HBL5461GY
	Ivory	HBL5661I	HBL5461I
	Red	—	HBL5461R
	White	—	HBL5461W
Isolated ground ^Δ .	Orange	IG5661	IG5461
Panel mount 1.94 in. (49.3) centers.	Brown	HBL5684	—
Ring terminal connection.	Brown	HBL5661RT	—
Duplex and Single Panel Mount			
Flush, nylon duplex face, side wired only.	Brown	HBL5652	—
	Ivory	HBL5652I	—
Panel mount 1.75 in. (44.5) centers.	Brown	HBL5658	—



HBL5662I



HBL5658

Note: ^ΔSee section O for additional information on isolated ground devices.

HP ratings are AC only.

See page B-53 for accessories.

See section P for wallplates.

Dimensions in Inches (mm)