

Insulgrip® Plugs and Connector Bodies



HBL5266C



HBL5269C

Specifications

Plugs	Part	Description
Typical Specification – Catalog No. HBL5266C Manufacturer's Identification – Hubbell HBL5266C Description – Straight Body Plug Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Verified to Fed. Spec. WC596 Certification – UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280 IP Suitability – IP20	Plug Housing Blade Holder Retainer Cord Clamp Contact Blades Ground Contact Blade Line Terminal Screws Ground Screw Wire Clamps	15A Nylon – Black Nylon – Natural Polycarbonate – Clear Nylon – Natural .060 in. (1.5) Brass .040 in. (1.0) Copper Alloy #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive (Green) .062 in. (1.6) Steel – Nickel Finish
Receptacles	Part	Description
Typical Specification – Catalog No. HBL5269C Manufacturer's Identification – Hubbell HBL5269C Description – Straight Body Connector Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Verified to Fed. Spec. WC596 Certification – UL Listed to UL498 File E1706, CSA Certified to C22.2 No. 42 File 280 IP Suitability – IP20	Connector Body Housing Contact Holder Retainer Cord Clamp Power Contacts Line Terminal Screws Ground Screw Wire Clamps	15A Nylon – Black Nylon – Natural Polycarbonate – Clear Nylon – Natural .040 in. (1.0) Copper Alloy #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive (Green) .062 in. (1.6) Steel – Nickel Finish

Performance

Electrical	
Dielectric Voltage Max. Working Voltage Current Interrupting Temperature Rise	Withstands 2,000V minimum. 125V or 250V as rated. Certified for current interrupting at full rated current. Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification Terminal Accommodation Product Identification Torque Range Cord Diameter Range	Terminals identified in accordance with UL498 and CSA (Brass, White, Green). #18-10 AWG copper conductors only. #16-10 AWG For EdgeConnect devices. Ratings are a permanent part of the device. 12 in./lb. terminal screws, 7 in./lb. assembly screws. .230–.720 in. (5.8–18.3) integral cord grip.
Environmental – Material	
Flammability Operating Temperature	UL 94HB or better. Maximum continuous 75°C; minimum – 40°C (w/o impact).

Dimensions in Inches (mm)