

15 and 20 Ampere, 125 Volts



15A 125V  
NEMA 5-15R  
UL CSA  
0.5 HP




20A 125V  
NEMA 5-20R  
UL CSA  
1 HP




**Commercial Specification Grade Receptacles**

Duplex	Color	Catalog Number	
Smooth polycarbonate face, duplex, side wired only.	Black	<b>CR15BLK</b>	<b>CR20BLK</b>
	Brown	<b>CR15</b>	<b>CR20</b>
	Gray	<b>CR15GRY</b>	<b>CR20GRY</b>
	Ivory	<b>CR15I</b>	<b>CR20I</b>
	Light Almond	<b>CR15LA</b>	<b>CR20LA</b>
	Red	—	<b>CR20R</b>
	White	<b>CR15WHI</b>	<b>CR20WHI</b>
Tamper-Resistant, smooth polycarbonate face, duplex, side wired only.	Black	<b>CR15BLKTR</b>	<b>CR20BLKTR</b>
	Brown	<b>CR15TR</b>	<b>CR20TR</b>
	Gray	<b>CR15GRYTR</b>	<b>CR20GRYTR</b>
	Ivory	<b>CR15ITR</b>	<b>CR20ITR</b>
	Light Almond	<b>CR15LATR</b>	<b>CR20LATR</b>
	Red	—	<b>CR20RTR</b>
	White	<b>CR15WHITR</b>	<b>CR20WHITR</b>
Finder groove, polycarbonate face, duplex, side wired only.	Black	—	<b>CRF20BLK</b>
	Brown	<b>CRF15</b>	<b>CRF20</b>
	Gray	<b>CRF15GRY</b>	<b>CRF20GRY</b>
	Ivory	<b>CRF15I</b>	<b>CRF20I</b>
	Light Almond	<b>CRF15LA</b>	<b>CRF20LA</b>
	White	<b>CRF15WHI</b>	<b>CRF20WHI</b>


Note: See page B-53 for accessories.  
See page Tech-10 for Tamper-Resistant descriptions.  
See section P for wallplates.



**CR15I**



**CR15TR**



**CRF15LA**

Dimensions in Inches (mm)