

15 and 20 Ampere, 125 Volts



15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP




Commercial Specification Grade Receptacles


Style Line® Decorator	Color	Catalog Number	
Smooth polycarbonate face, Style Line decorator duplex, back and side wired.	Black	DR15BLK	DR20BLK
	Brown	DR15	DR20
	Gray	DR15GRY	DR20GRY
	Green	DR15GN	DR20GN
	Ivory	DR15I	DR20I
Tamper-Resistant, Style Line decorator duplex, smooth polycarbonate face, back and side wired.	Light Almond	DR15LA	DR20LA
	Red	DR15R	DR20R
	White	DR15WHI	DR20WHI
	Black	DR15BLKTR	DR20BLKTR
	Brown	DR15TR	DR20TR
Weather and Tamper-Resistant, Style Line decorator duplex, smooth polycarbonate face, back and side wired.	Gray	DR15GRYTR	DR20GRYTR
	Green	DR15GNTR	DR20GNTR
	Ivory	DR15ITR	DR20ITR
	Light Almond	DR15LATR	DR20LATR
	White	DR15WHITR	DR20WHITR
Nightlight receptacle, two nightlight sources for a total of 0.5 Lumens, Tamper-Resistant shutters complies with NEC article 406.12, back and side wired.	Black	DR15BLKWTRTR	DR20BLKWTRTR
	Brown	DR15WRTR	DR20WRTR
	Gray	DR15GRYWRTR	DR20GRYWRTR
	Ivory	DR15WRTR	DR20WRTR
	Light Almond	DR15LAWTRTR	DR20LAWTRTR
	White	DR15WHIWRTR	DR20WHIWRTR
	Ivory	DR15NLIV	—
	Light Almond	DR15NLLA	—
	White	DR15NLWH	—




DR15GRY



DR20ITR



DR20GRYWRTR



DR15NLIV

Note: See page B-53 for accessories.
See page Tech-10 for Tamper and Weather Resistant descriptions.
See section P for wallplates.

Dimensions in Inches (mm)