

TWIST-LOCK® AND HUBBELLOCK® DEVICES

Midget Connector Bodies and Flanged Receptacles

C
SECTION

IP20
SUITABILITY



Connector Bodies

Description	Cord Dia.	Catalog Number		
		15A 125V NEMA ML-1R	15A 125V NEMA ML-2R	15A 125/250V AC NEMA ML-3R
Valise® connector body, black nylon, polarized, multiple drive screws.	.220"-.385" (5.6-9.8)	HBL7464V*	—	—
Valise connector body, black nylon, insulation displacement terminals.	.300"-.430" (7.6-10.9)	—	HBL7593V	—
Black nylon cover, phenolic body, screw terminals.	.281"-.421" (7.1-10.7)	—	HBL7593	—
Angle connector body, black nylon cover, phenolic body, screw terminals.	.335"-.421" (8.5-10.7)	—	HBL7571	—
Valise type, black nylon, with insulation displacement terminals.	.300"-.430" (7.6-10.9)	—	—	HBL7484V*
Black nylon body, phenolic base, cord grip.	.281"-.421" (7.1-10.7)	—	—	HBL7484*
Same as above, except for angle cord grip.	.335"-.421" (8.5-10.7)	—	—	HBL7433*



HBL7464V



HBL7593V



HBL7593



HBL7571



HBL7484V

Flanged Receptacles

Description	Catalog Number		
Stainless steel flange, exposed terminals.	HBL7468*	—	—
Exposed terminals, black nylon flange.	—	HBL7596N	—
Exposed terminals, stainless steel flange.	—	HBL7596	—
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in dia.	—	HBL7598	—
Exposed terminals, black nylon flange.	—	—	HBL7487N*
Exposed terminals, stainless steel flange.	—	—	HBL7487*
Covered terminals, stainless steel flange, accepts cord .500" (12.7) in diameter.	—	—	HBL7489*

Note: See page C-8 for accessories.

*UL Listed only.

Female ML-2R devices have solid center ground pins.

Female ML-3R devices have hollow center neutral sleeves.




HBL7596



HBL7598



HBL7596N



HBL7468

Dimensions in Inches (mm)