




**30A, 125V,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	<b>HBL9308</b>	—
Receptacle, orange, isolated ground <sup>Δ</sup> .	-	<b>IG9308</b>	—
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.1)	—	<b>HBL9309*</b>



**30A, 125V,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**



Description	Cord Diameter	Catalog Number	
Receptacle, black RTP. Travel Trailer use only.	-	<b>HBLTT30R</b>	—
Plug, nylon, angle. Travel Trailer use only.	.625"-1.187" (15.9-30.1)	—	<b>HBLTT30P</b>



**30A, 250V,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY



Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	<b>HBL9330</b>	—
Receptacle, orange, isolated ground <sup>Δ</sup> .	-	<b>IG9330</b>	—
Plug, nylon, angle, 4-position	.625"-1.187" (15.9-30.1)	—	<b>HBL9331*</b>




**30A, 277V AC,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY



Description	Cord Diameter	Catalog Number	
Receptacle, black RTP.	-	<b>HBL9315</b>	—
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.1)	—	<b>HBL9319*</b>




**30A, 125/250V,  
3 Pole, 3 Wire Non-Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY



Description	Cord Diameter	Catalog Number	
Receptacle, black phenolic.	-	<b>HBL9350</b>	—
Receptacle, surface mount aluminum housing.	-	<b>HBL9395</b>	—
Plug, Insulgrip®, nylon.	.625"-1.00" (15.9-25.4)	—	<b>HBL9337C</b>
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.1)	—	<b>HBL9333</b>



Note: RTP is an abbreviation for reinforced thermoplastic polyester.  
<sup>Δ</sup>See section O for additional information on isolated ground devices.  
 \*Not Fed. Spec. Listed.  
 See page B-55 for accessories.

Dimensions in Inches (mm)