

**HBL® Extra Heavy Duty Max, Straight Blade Specification Grade Duplex Receptacles**



**HBL5262**

**Specifications**

Receptacles	Part	Description
Typical Specification – Catalog No. <b>HBL5262</b> Manufacturer's Identification – Hubbell <b>HBL5262</b> Description – Heavy Duty Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire, Grounding Rating – 15A, 125V Certification: UL Listed to UL498 File E2186, Guide RTRT Fed. Spec. WCS96, Meets NEMA® WD-6 Compliant Certified to CSA, C22.2, No. 42 File 285	Receptacle Top Base By-Pass Power Contacts Wire Clamps Mounting Strap Line Terminal Screws Ground Screw Center Assembly Rivet Automatic Self-Grounding Clip Flat Head Mounting Screws Ground Tension Clips	15A Nylon RTP* .037 in. (.9) Brass .031 in. (.8) Brass .050 in. (1.3) Brass #10-32 Brass, Multiple Drive #10-32 Brass, Multiple Drive (Green) Brass Stainless Steel Steel-Zinc Plated Steel-Nickel Finish

**Performance**

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V or 250V as rated.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL 498 and CSA (Brass, White, Green).
Terminal Accommodation	#14-10 AWG stranded or solid copper conductor only.
Product Identification	Ratings are a permanent part of the device.
Environmental – Material	
Flammability	Top: UL 94V-2. Base: UL 94V-0 and UL 94-5 VA.
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact).

Note: \*Reinforced Thermoplastic Polyester.

NEMA is a registered trademark of the National Electrical Manufacturers Association.

Dimensions in Inches (mm)