

**50A, 125/250V,  
3 Pole, 4 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 125/250V  
NEMA 14-50R  
UL CSA  
3(2) HP



50A 125/250V  
NEMA 14-50P  
UL CSA  
3(2) HP



Description	Cord Diameter	Catalog Number	
EV Grade receptacle, weather resistant, black RTP.	-	HBL9450A	-
EV Grade plug, black and white nylon.	.625"-1.310" (15.9-33.3)	-	HBL9451C
EV Grade angle plug, 4-position, black and white nylon.	.625"-1.310" (15.9-33.3)	-	HBL9452C



HBL9450A

**50A, 3Ø 250V AC,  
3 Pole, 4 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 3Ø 250V AC  
NEMA 15-50R  
UL CSA  
7.5 HP




50A 3Ø 250V AC  
NEMA 15-50P  
UL CSA  
7.5 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	HBL8450A	-
Plug, nylon.	.625"-1.310" (15.9-33.3)	-	HBL8451C
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL8452C



HBL9451C



HBL9452C

**UL**  
**50A, 3ØY 120/208V AC,  
4 Pole, 4 Wire Non-Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 3ØY  
120/208V AC  
NEMA 18-50R  
UL Listed  
7.5 HP



50A 3ØY  
120/208V AC  
NEMA 18-50P  
UL Listed  
7.5 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	HBL8350A	-
Plug, nylon, angle, 4-position.	.625"-1.310" (15.9-33.3)	-	HBL8352C

Note: RTP is an abbreviation for reinforced thermoplastic polyester.  
See page B-55 and B-56 for accessories.



HBL8350A

Dimensions in Inches (mm)