



**50A, 125V,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 125V  
NEMA 5-50R  
UL CSA  
2 HP



50A 125V  
NEMA 5-50P  
UL CSA  
2 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	<b>HBL9360</b>	-
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	-	<b>HBL9361</b>



**HBL9361**

**50A, 250V,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 250V  
NEMA 6-50R  
UL CSA  
3 HP



50A 250V  
NEMA 6-50P  
UL CSA  
3 HP

Description	Cord Diameter	Catalog Number	
EV Grade receptacle, weather resistant, black RTP.	-	<b>HBL9367</b>	-
EV Grade angle plug, 4-position, black and white nylon.	.625"-1.187" (15.9-30.2)	-	<b>HBL9368</b>



**HBL9367**

**50A, 277V AC,  
2 Pole, 3 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




50A 277V AC  
NEMA 7-50R  
UL CSA  
5 HP



50A 277V AC  
NEMA 7-50P  
UL CSA  
5 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black RTP weather resistant.	-	<b>HBL9365</b>	-
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	-	<b>HBL9379</b>



**HBL9365**  
Representative of surface mount receptacle

**UL**  
**50A, 125/250V,  
3 Pole, 3 Wire Non-Grounding,  
Receptacles, Connector Body and Plugs**

**IP20**  
SUITABILITY



50A 125/250V  
NEMA 10-50R  
UL Listed  
3(2) HP



50A 125/250V  
NEMA 10-50P  
UL Listed  
3(2) HP

Description	Cord Diameter	Catalog Number	
Receptacle, black phenolic.	-	<b>HBL7962</b>	-
Receptacle, surface mount aluminum housing.	-	<b>HBL7940</b>	-
Connector body, Insulgrip®, nylon.	.625"-1.218" (15.9-30.9)	<b>HBL7515C</b>	-
Plug, Insulgrip, nylon.	.625"-1.218" (15.9-30.9)	-	<b>HBL7513C</b>
Plug, nylon, angle, 4-position.	.625"-1.187" (15.9-30.2)	-	<b>HBL7977</b>



**HBL7515C**



**HBL7513C**

Note: RTP is an abbreviation for reinforced thermoplastic polyester.  
See pages B-55 and B-56 for accessories.

Dimensions in Inches (mm)