

**HBL® Compact Heavy Duty Style Line®,  
Specification Grade and Hospital Grade  
Straight Blade Duplex Receptacles**



HBL2152

HBL2172

**Specifications**

Receptacles	Part	Description
Typical Specification – Catalog No. <b>HBL2152</b> Manufacturer's Identification – Hubbell <b>HBL2152</b> Receptacle Description – Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire Grounding Rating – 15A, 125V Certification – UL File No. E2186 Certified to CSA File No. 285	Receptacle Top Base Triple Wipe Power Contacts Wire Clamp Mounting Strap Ground Contact Line Terminal Screws Ground Screw Automatic Self-Grounding Staple Mounting Screws	15A Nylon RTP* .031 in. (.8) Brass .062 in. (1.8) Steel-Nickel Finish .050 in. (1.3) Galvanized Steel .031 in. (.8) Brass #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive Stainless Steel Zinc Plated Steel
Receptacles	Part	Description
Typical Specification – Catalog No. <b>HBL2172</b> Manufacturer's Identification – Hubbell HBL2182 Receptacle Description – Straight Blade Duplex Receptacle Type – 2 Pole, 3 Wire Grounding Rating – 15A, 125V Certification – UL Listed to UL498 File E2186, Fed. Spec. WC596, Certified to CSA File No. 285	Receptacle Top Base Triple Wipe Power Contacts Wire Clamp Mounting Strap Ground Contact Line Terminal Screws Ground Screw Automatic Self-Grounding Staple Mounting Screws	15A Nylon RTP* .031 in. (.8) Brass .062 in. (1.8) Steel-Nickel Finish .050 in. (1.3) Galvanized Steel .031 in. (.8) Brass #8-32 Brass, Multiple Drive #8-32 Brass, Multiple Drive Stainless Steel Zinc Plated Steel

**Performance**

Electrical	
Dielectric Voltage	Withstands 2,000V minimum.
Max. Working Voltage	125V.
Current Interrupting	Certified for current interrupting at full rated current.
Temperature Rise	Max 30°C temperature rise at full rated current after 50 cycles of overload at 150% of rated current at a power factor of 75%.
Mechanical	
Terminal Identification	Terminals identified in accordance with UL 498 and CSA (Brass, White, Green).
Terminal Accommodation	#14-10 AWG stranded or solid copper conductor only.
Product Identification	Ratings are a permanent part of the device.
Environmental – Material	
Flammability	UL 94V-2.
Operating Temperature	Maximum continuous 75°C; minimum -40°C (w/o impact).

Note: \*Reinforced Thermoplastic Polyester.

Please consult the factory for product dimensions and specifications of other products listed in this catalog.

Dimensions in Inches (mm)