



**20A, 125/250V,  
3 Pole, 3 Wire Non-Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




20A 125V/250V  
NEMA 10-20R  
UL Listed  
2(1) HP



20A 125V/250V  
NEMA 10-20P  
UL Listed  
2(1) HP

Description	Cord Diameter	Catalog Number	
Receptacle, black phenolic.	-	<b>HBL6810</b>	-
Plug, Insulgrip®, nylon.	.385"-.780" (9.8-19.8)	-	<b>HBL9977C</b>

Note: Horsepower ratings listed above are AC only.  
Horsepower ratings not in parentheses are phase to phase (208 to 240V AC).  
Those in parentheses are phase to neutral (120V AC).  
See pages B-53 and B-54 for accessories.



**HBL6810**



**20A, 125/250V,  
3 Pole, 4 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY



20A 125V/250V  
NEMA 14-20R  
UL CSA  
2(1) HP




20A 125V/250V  
NEMA 14-20P  
UL CSA  
2(1) HP

Description	Cord Diameter	Catalog Number	
Receptacle, black nylon body, back and side wired.	-	<b>HBL8410</b>	-
Plug, nylon, angle 4-position.	.390"-.775" (9.9-19.7)	-	<b>HBL8411C</b>

Note: See pages B-53 and B-54 for accessories.



**HBL9977C**



**HBL8410**



**20A, 3Ø 250V AC,  
3 Pole, 4 Wire Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY




20A 3Ø 250V AC  
NEMA 15-20R  
UL CSA  
3 HP




20A 3Ø 250V AC  
NEMA 15-20P  
UL CSA  
3 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black nylon body, back and side wired.	-	<b>HBL8420</b>	-
Plug, nylon, angle 4-position.	.390"-.775" (9.9-19.7)	-	<b>HBL8421C</b>

Note: Horsepower ratings listed above are AC only.  
Horsepower ratings not in parentheses are phase to phase (208 to 240V AC).  
Horsepower ratings in parentheses are phase to neutral (120V AC).  
See pages B-53 and B-54 for accessories.



**HBL8411C**



**HBL8420**



**20A, 3ØY 120/208V AC,  
4 Pole, 4 Wire Non-Grounding,  
Receptacles and Plugs**

**IP20**  
SUITABILITY



20A 3ØY 120/208V AC  
NEMA 18-20R  
UL Listed  
2 HP



20A 3ØY 120/208V AC  
NEMA 18-20P  
UL Listed  
2 HP

Description	Cord Diameter	Catalog Number	
Receptacle, black nylon body.	-	<b>HBL7250</b>	-
Plug, nylon, angle, 4-position.	.390"-.775" (9.9-19.7)	-	<b>HBL7251C</b>

Note: Horsepower ratings are phase to phase (208 to 240V AC).  
Weatherproof boots for plugs not available.  
See pages B-53 and B-54 for accessories.



**HBL7251C**

Dimensions in Inches (mm)