

SKU: 44171-B2

UPC:



Features & Benefits:

Description:ILSCON Ring Terminal, Conductor Size 1/0, 5/16in Bolt Size, Non-Insulated, Pack of 2

Specs

Additional Class Attributes

| | |
|--------------------------|-------------|
| Conductor Entry | Funnel wire |
| Connection | Compression |
| Construction Type | Brazed |
| Insulation Flared End | No |
| Insulation Grip | No |
| Mounting Hole Type | Thru |
| Number of Conductors | 1 |
| Number of Mounting Holes | 1 |
| Tongue Type | Ring |

Dimensions

| | |
|----------------|--------|
| Height (IN) | 0 |
| Height BX (IN) | 2 |
| Length (IN) | 0 |
| Weight (LB) | 0.083 |
| Weight BX (LB) | 0.977 |
| Width (IN) | 0 |
| Width BX (IN) | 6.1875 |

Material and Finish

| | |
|---------------------|--------|
| Conductor Material | Copper |
| Connector Finish | Tin |
| Fully Insulated | No |
| Insulation Material | None |
| Material | Copper |

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 2 |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated | No |
| NEMA Code | S-588-3 |
| UPC Code | 78366944207 |

Bolt and Screw Sizes

| | |
|-------------------------|------|
| Mounting Bolt/Stud Size | 5/16 |
|-------------------------|------|

Testing Standards

| | |
|-------------------|---|
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number | NA |
| UL File Number | NA |

Color

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Conductor Ranges

| | |
|--|---------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | NA |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 1/0 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |

Environment and Temperature

| | |
|--------------------|------|
| Halogen Free | NA |
| Temperature Rating | 90°C |