

SKU: 44620-B20

UPC:



Features & Benefits:

Description:ILSCON Parallel Splice, Conductor Range 10-12, Non-insulated, Yellow Color Code, Bag of 20

Specs

Additional Class Attributes

| | |
|-----------------------|-----------------|
| Conductor Entry | Funnel wire |
| Connection | Compression |
| Connector Type | Parallel Splice |
| Insulation Flared End | No |
| Mounting Hole Type | NA |
| Number of Conductors | 2 |

Dimensions

| | |
|---------------------------------------|--------|
| Height (IN) | 0 |
| Height BX (IN) | 2 |
| Length (IN) | 0.33 |
| Length (mm) | 8.382 |
| Maximum Wire Insulation Diameter (IN) | NA |
| Weight (LB) | 0.135 |
| Weight BX (LB) | 1.497 |
| Width (IN) | 0 |
| Width BX (IN) | 6.1875 |

Material and Finish

| | |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish | Tin |
| Fully Insulated | No |
| Insulation | None |
| Material | Copper |

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 20 |
| Carton Quantity Description | STD PACK QTY 10 |
| Dual Rated | No |
| NEMA Code | S-588-3 |
| UPC Code | 78366944335 |

Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

NA

UL File Number

NA

Color

Color

Silver

Color Code

Yellow

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)

NA

Conductor Range AL Stranded (Primary, run, main, line)

NA

Conductor Range AL Stranded (Secondary, tap, load)

NA

Conductor Range CU Solid (Primary, run, main, line)

10 Sol - 12 Sol

Conductor Range CU Solid (Secondary, tap, load)

NA

Conductor Range CU Stranded (Primary, run, main, line)

10 Str - 12 Str

Conductor Range CU Stranded (Secondary, tap, load)

NA

Conductor Range AL Solid (Primary, run, main, line)

NA

Environment and Temperature

Halogen Free

NA

Temperature Rating

90°C