



SKU: 45320-B10

UPC:

Features & Benefits:

Description:ILSCON Disconnect Terminal, Conductor Range 10-12, Flag, Ring, #10 Bolt Size, Non-Insulated, Pack of 10

Specs

Additional Class Attributes

Conductor Entry	Funnel wire
Connection	Compression
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	1
Tongue Type	Ring flag

Dimensions

Height (IN)	0
Height BX (IN)	2
Length (IN)	0.375
Length (mm)	9.525
Maximum Wire Insulation Diameter (IN)	NA
Mounting Bolt/Stud Size (mm)	254
Weight (LB)	0.125
Weight BX (LB)	1.397
Width (IN)	0.6875
Width BX (IN)	6.1875
Width (mm)	17.4625

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Fully Insulated	No
Insulation	None
Material	Copper

General

Bag Quantity	10
Carton Quantity Description	STD PACK QTY 10
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366945126

Bolt and Screw Sizes

Mounting Bolt/Stud Size

#10

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line) 10 Sol - 12 Sol

Conductor Range CU Stranded (Primary, run, main, line) 10 Str - 12 Str

Testing Standards

Prop65 Compliance

This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation

UL Control Number

NA

UL File Number

NA

Color

Color

Silver