



**SKU:** AH-6

**UPC:** 0783669004106

**Features & Benefits:**

**Description:** Aluminum Compression Tap, Main Range 500-4/0, Tap Range 2/0-6, Tin Plated, UL

## Specs

### Additional Class Attributes

Barrel Marking	Ink
Fixing Type	NA
ILSCOs Die Index Number	N
Replacement Part(s)	NA

### Dimensions

Height (IN)	1.278
Height BX (IN)	3.5
Height (mm)	32.4612
Length (IN)	2.826
Length (mm)	71.7804
Weight (LB)	0.345
Weight BX (LB)	3.712
Width (IN)	2
Width BX (IN)	5.875
Width (mm)	50.8

### Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-1
UPC Code	78366900410

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

### Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E158587

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
Color Code	Red

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 4/0 Str
Conductor Range AL Stranded (Secondary, tap, load)	2/0 Str - 6 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 4/0 Str
Conductor Range CU Stranded (Secondary, tap, load)	2/0 Str - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

### Voltage

Voltage Rating	35 kV
Voltage Rating with cover	NA