



SKU: AK-4

UPC: 0783669008319

Features & Benefits:

Description: Aluminum Split Bolt, Main Range 4-8, Tap Range 4-10, Tin Plated, UL, CSA

Specs

Additional Class Attributes

| | |
|----------------------|------------|
| Connection | Mechanical |
| Number of Conductors | 1 |
| Number of Poles | 1 |

Dimensions

| | |
|-----------------|--------------|
| Drive Size Main | 13/16 |
| Drive Type Main | External Hex |
| Height (IN) | 0.62 |
| Height BX (IN) | 2.75 |
| Length (IN) | 1.58 |
| Weight (LB) | 0.0438 |
| Weight BX (LB) | 5.427 |
| Width (IN) | 0.81 |
| Width BX (IN) | 6 |

Material and Finish

| | |
|--------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish | Tin |
| Insulation | NA |
| Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|--|-----|
| Number of Wire Binding Screws per Port | 1 |
| Wire Binding Screw Size | NA |
| Wire Binding Torque | 165 |

General

| | |
|--------------|---|
| Bag Quantity | 1 |
|--------------|---|

| | |
|------------------------------------|------------------|
| Carton Quantity Description | STD PACK QTY 100 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | S-588-4 |
| UPC Code | 78366900831 |

Testing Standards

| | |
|---------------------------------|---|
| CSA File Number | 72632 |
| CSA Standard | C22.2 No. 188 |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number | 670B |
| UL / CULUS Specification | UL 486A/B Listed |
| UL File Number | E6207 |

Environment and Temperature

| | |
|---------------------------|------|
| Temperature Rating | 90°C |
|---------------------------|------|

Color

| | |
|--------------|--------|
| Color | Silver |
|--------------|--------|

Conductor Ranges

| | |
|---|----------------|
| Conductor Range AL Solid (Secondary, tap, load) | 4 Sol - 10 Sol |
| Conductor Range AL Stranded (Primary, run, main, line) | 4 Str - 8 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | 4 Str - 10 Str |
| Conductor Range CU Solid (Primary, run, main, line) | 4 Sol - 8 Sol |
| Conductor Range CU Solid (Secondary, tap, load) | 4 Sol - 10 Sol |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 8 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | 4 Str - 10 Str |
| Conductor Range AL Solid (Primary, run, main, line) | 4 Sol - 8 Sol |

Voltage

| | |
|-----------------------|-------|
| Voltage Rating | 35 kV |
|-----------------------|-------|