


**SKU:** ASL-250

**UPC:** 0783669010183

**Features & Benefits:**

**Description:** Aluminum Stacking Adapter, Conductor Range 1/0-250, Tin Plated, UL



## Specs

### Additional Class Attributes

|                          |        |
|--------------------------|--------|
| Barrel Marking           | Hard   |
| Flared End               | No     |
| Mounting Method          | Bolted |
| Number of Mounting Holes | 2      |
| Sight Window             | No     |
| Slotted                  | No     |

### Dimensions

|                        |        |
|------------------------|--------|
| Height (IN)            | 0.75   |
| Height BX (IN)         | 2.25   |
| Length (IN)            | 3      |
| Max Insulation OD (IN) | 0.868  |
| Weight (LB)            | 0.1535 |
| Weight BX (LB)         | 2.435  |
| Width (IN)             | 1      |
| Width BX (IN)          | 5      |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Copper   |
| Connector Finish   | Tin      |
| Material           | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 10 |
| Direct Burial               | No              |
| Dual Rated                  | Yes             |
| NEMA Code                   | 0-000-1         |
| UPC Code                    | 78366901018     |

### **Bolt and Screw Sizes**

|                         |            |
|-------------------------|------------|
| Mounting Bolt/Stud Size | 1/2 to 5/8 |
|-------------------------|------------|

### **Testing Standards**

|                          |   |
|--------------------------|---|
| CSA File Number          | NA  |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | IND   |
| UL Control Number        | 453G  |
| UL / CULUS Specification | UL 486A/B Listed  |
| UL File Number           | E6207   |

### **Environment and Temperature**

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### **Color**

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### **Conductor Ranges**

|  |                     |
|--|---------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                  |
| Conductor Range AL Stranded (Primary, run, main, line) | 250 kcmil - 1/0 Str |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA                  |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                  |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                  |
| Conductor Range CU Stranded (Primary, run, main, line) | 250 kcmil - 1/0 Str |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA                  |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                  |

### **Voltage**

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|