



SKU: BGC-1A

UPC: 0783669010022

Features & Benefits:

Description: Permagraund Bronze Ground Clamp, Conductor Range 4-8, Pipe Sizes 1/2 to 1in

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Parallel

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
NPS/IPS Pipe Size	7/8

Dimensions

Drive Size Main	NA
Height (IN)	0
Height BX (IN)	3.625
Length (IN)	0
Weight (LB)	0.1518
Weight BX (LB)	4.049
Width (IN)	0
Width BX (IN)	6.375

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Cast bronze

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 25
Direct Burial	No
Dual Rated	No
NEMA Code	S-573-2
UPC Code	78366901002

Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 41
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	8M24
UL / CULUS Specification	UL 467 Listed
UL File Number	E158587