



**SKU:** BGRC-58

**UPC:** 0783669009965

**Features & Benefits:**

**Description:** Permaground Bronze Ground Rod Clamp, Conductor Range 1/0-8, Ground Rod Size 5/8in, Direct Bury

## Specs

### Additional Class Attributes

|                            |            |
|----------------------------|------------|
| Connection                 | Mechanical |
| Number of Conductors       | 1          |
| Number of Ports / Wireways | 1          |
| Wire Orientation           | Parallel   |

### Conductor Ranges

|  |                 |
|--|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | NA              |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | NA              |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |
| Conductor Range Solid with Ground Rod                  | NA              |
| Conductor Range Solid with Rebar                       | NA              |
| Conductor Range Str with Ground Rod                    | 1/0 Str - 8 Str |
| Conductor Range Str with Rebar                         | 1/0 Str - 8 Str |
| Conductor Size with Ground Rod                         | 3 Str           |
| Conductor Size with Rebar                              | 7 Str           |
| Ground Rod Size  | 5/8             |
| Rebar Size(s) Main                                     | #5 (5/8)        |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 1/2          |
| Drive Type Main | External Hex |
| Height (IN)     | 1.616        |
| Height BX (IN)  | 2.0625       |
| Height (mm)     | 41.0464      |
| Length (IN)     | 0.925        |
| Length (mm)     | 23.495       |
| Weight (LB)     | 0.13         |
| Weight BX (LB)  | 4.47         |
| Width (IN)      | 1.031        |
| Width BX (IN)   | 5.062        |
| Width (mm)      | 26.1874      |

### Material and Finish

|                    |             |
|--------------------|-------------|
| Conductor Material | Copper      |
| Connector Finish   | NA          |
| Insulation         | NA          |
| Material           | Cast bronze |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|  |    |
|--|----|
| Number of Wire Binding Screws per Port | 1  |
| Wire Binding Screw Size                | NA |

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial               | Yes             |
| Dual Rated                  | No              |
| NEMA Code                   | S-573-2         |
| UPC Code                    | 78366900996     |

### Testing Standards

|                          |   |
|--------------------------|---|
| CSA File Number          | LR-29601  |
| CSA Standard             | C22.2 No. 65-03   |
| Prop65 Compliance        | WARNING: Cancer and Reproductive Harm -<br><a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number        | 667P  |
| UL / CULUS Specification | UL 467 Listed   |
| UL File Number           | E34440  |