



SKU: CCS-6

UPC: 0783669032017

Features & Benefits:

Description: Copper Compression Sleeve, Conductor Size 6, Flared End, Tin Plated

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Flared End	Yes
ILSCOs Die Index Number	NA
Installing Dies	NA
Sight Window	No
Slotted	No

Dimensions

Height (IN)	0.374
Height BX (IN)	2.25
Height (mm)	9.4996
Inside Diameter (IN)	0.232
Inside Diameter (mm)	5.8928
Length (IN)	1.16
Length (mm)	29.464
Outside Diameter (IN)	0.314
Outside Diameter (mm)	7.9756
Weight (LB)	0.014
Weight BX (LB)	0.779
Width (IN)	0.374
Width BX (IN)	4.375
Width (mm)	9.4996

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366903201

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	AP-100973-1
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	8M24
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E158587

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	Blue

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	6 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	35 kV
----------------	-------