



SKU: CSWS-750-38

UPC: 0783669648935

Features & Benefits:

Description: Surecrimp Copper Compression Lug, Conductor Size 750, 1 Hole, 3/8in Bolt Size, Standard Barrel, Sight Window, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-106
ILSCOs Die Index Number	I-106
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

Dimensions

Barrel Length (IN)	1.5
Barrel Length (mm)	38.1
Dimension G (IN)	0.414
Dimension G (mm)	10.5156
Height (IN)	1.358
Height BX (IN)	2
Height (mm)	34.4932
Inside Diameter (IN)	1.031
Inside Diameter (mm)	26.1874
Length (IN)	3.652
Length (mm)	92.7608
Mounting Bolt/Stud Size (mm)	965.2
Mounting Hole Diameter (IN)	0.406
Mounting Hole Diameter (mm)	10.3124
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	1.313
Outside Diameter (mm)	33.3502
Strip Length (mm)	39.6748
Tang Length (IN)	1.25
Tang Length (mm)	31.75
Tang Thickness (IN)	0.282
Tang Thickness (mm)	7.1628

Tang Width (IN)	1.901
Tang Width (mm)	48.2854
Weight (LB)	0.581670011507631
Weight BX (LB)	3.3636
Width (IN)	1.901
Width BX (IN)	6.1875
Width (mm)	48.2854

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	750 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	750 kcmil - 500 kcmil
Flex Conductor Range	600 G,H,I,M 646.4 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366964893

Bolt and Screw Sizes

Mounting Bolt/Stud Size	3/8
-------------------------	-----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating

90°C

Color

Color

Silver

Color Code

Black

Voltage

Voltage Rating

35 kV