



**SKU:** CT-250

**UPC:** 0783669122435

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Sleeve, Conductor Size 250, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-62
ILSCOs Die Index Number	I-62
Number of Conductors	1
Sight Window	No
Slotted	No

### Dimensions

Height (IN)	0.75
Height BX (IN)	2.25
Height (mm)	19.05
Inside Diameter (IN)	0.594
Inside Diameter (mm)	15.0876
Length (IN)	2.25
Length (mm)	57.15
Outside Diameter (IN)	0.75
Outside Diameter (mm)	19.05
Weight (LB)	0.117
Weight BX (LB)	1.6051
Width (IN)	0.75
Width BX (IN)	5
Width (mm)	19.05

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	250 kcmil - 1/0 Str
Flex Conductor Range	4/0 G,H,I,K,M,DLO

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Flex
----------------	------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366912243

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Silver
Color Code	Yellow

### Voltage

Voltage Rating	35 kV
----------------	-------