



SKU: CT-350

UPC: 0783669123661

Features & Benefits:

Description: Surecrimp Copper Compression Sleeve, Conductor Size 350, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Standard
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-71
ILSCOs Die Index Number	I-71
Number of Conductors	1
Sight Window	No
Slotted	No

Dimensions

Height (IN)	0.89
Height BX (IN)	2.25
Height (mm)	22.606
Inside Diameter (IN)	0.703
Inside Diameter (mm)	17.8562
Length (IN)	2.375
Length (mm)	60.325
Outside Diameter (IN)	0.89
Outside Diameter (mm)	22.606
Weight (LB)	0.228
Weight BX (LB)	2.2728
Width (IN)	0.89
Width BX (IN)	5
Width (mm)	22.606

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	350 kcmil - 3/0 Str
Flex Conductor Range	250 I,K,M 262.2 DLO

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366912366

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	Red

Voltage

Voltage Rating	35 kV
----------------	-------