



SKU: CTL-1000

UPC: 0783669153484

Features & Benefits:

Description: Surecrimp Copper Compression Sleeve, Conductor Size 1000, Long Barrel, Tin Plated, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-125
ILSCOs Die Index Number	I-125
Number of Conductors	1
Sight Window	No
Slotted	No

Dimensions

Height (IN)	1.5
Height BX (IN)	2
Height (mm)	38.1
Inside Diameter (IN)	1.172
Inside Diameter (mm)	29.7688
Length (IN)	6.125
Length (mm)	155.575
Outside Diameter (IN)	1.5
Outside Diameter (mm)	38.1
Weight (LB)	1.559
Weight BX (LB)	4.8265
Width (IN)	1.5
Width BX (IN)	6.1875
Width (mm)	38.1

Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	1000 kcmil - 750 kcmil
Flex Conductor Range	750 G,H,I 777.7 DLO

Material and Finish

Conductor Material	Copper
Connector Finish Material	Tin
Material	Copper

Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-1
UPC Code	78366915348

Bolt and Screw Sizes

Mounting Bolt/Stud Size	NA
-------------------------	----

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
Color Code	White

Voltage

Voltage Rating	35 kV
----------------	-------