



**SKU:** DBA-1000S

**UPC:** 0783669232097

**Features & Benefits:**

**Description:** Aluminum Two-Bolt Split Bolt, Dual Rated, Main Conductor Range 1000-500, Tap Range 1000-3/0, Wax Plated, Includes Spacer Bar

## Specs

### Additional Class Attributes

Connection	Mechanical
Includes	Connector, spacer
Number of Conductors	2
Number of Poles	1

### Dimensions

Drive Size Main	15/16
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	2.75
Length (IN)	0
Weight (LB)	1.5492
Weight BX (LB)	4.8946
Width (IN)	0
Width BX (IN)	6

### Material and Finish

Conductor Material	Copper
Connector Finish	Wax
Insulation	NA
Material	Aluminum
Wire Binding Hardware Finish	Aluminite 205
Wire Binding Hardware Material	Aluminum

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	5/8

## General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366923209

## Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	NA
UL File Number	NA

## Environment and Temperature

Temperature Rating	NA
--------------------	----

## Color

Color	Silver
-------	--------

## Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	1000 kcmil - 3/0 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1000 kcmil - 500 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	1000 kcmil - 3/0 Str