



SKU: GBL-250-B2

UPC:

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 250-6, Tin Plated, Bag of 2

Specs

Additional Class Attributes

Connection	Mechanical
Number of Ports / Wireways	1

Dimensions

Drive Size Main	7/32
Drive Type Main	Internal Hex
Height (IN)	0.88
Height BX (IN)	2.75
Height (mm)	22.352
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.382077181868232
Weight BX (LB)	4.303
Width (IN)	4
Width BX (IN)	6
Width (mm)	101.6

Material and Finish

Connector Finish	Tin
Material	Aluminum
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Bolt and Screw Sizes

Wire Binding Torque	250 kcmil - 4 AWG = 150
---------------------	-------------------------

General

Bag Quantity	2
Carton Quantity Description	STD PACK QTY 10
Direct Burial	No
NEMA Code	S-588-3
UPC Code	78366996016

Conductor Ranges

Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	250 kcmil - 6 Str

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	NA
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440