




**SKU:** GBL-4DBT

**UPC:** 0783669960181

**Features & Benefits:**

**Description:**Permaground Copper Lay-in Groud Lug, Conductor Size 4-14, #10 Bolt Size, Slotted Head, Tin Plated

## Specs

### Additional Class Attributes

|                              |            |
|------------------------------|------------|
| Connection                   | Mechanical |
| Mounting Hole Type           | Thru       |
| Mounting Kit Hardware Part # | GBL-MH1    |
| Number of Conductors         | 1          |
| Number of Mounting Holes     | 1          |
| Number of Ports / Wireways   | 1          |
| Wire Orientation             | NA         |

### Dimensions

|                              |         |
|------------------------------|---------|
| Drive Size Main              | NA      |
| Drive Type Main              | Slotted |
| Height (IN)                  | 0.825   |
| Height BX (IN)               | 2.25    |
| Length (IN)                  | 1.15    |
| Mounting Bolt/Stud Size (mm) | 254     |
| Mounting Hole Diameter (IN)  | 0.218   |
| Mounting Hole Diameter (mm)  | 5.5372  |
| Tang Length (IN)             | 0.47    |
| Tang Length (mm)             | 11.938  |
| Tang Thickness (IN)          | 0.185   |
| Tang Thickness (mm)          | 4.699   |
| Tang Width (IN)              | 0.375   |
| Tang Width (mm)              | 9.525   |
| Weight (LB)                  | 0.06    |
| Weight BX (LB)               | 3.9     |
| Width (IN)                   | 0.375   |
| Width BX (IN)                | 5       |

### Material and Finish

|                                |                                |
|--------------------------------|--------------------------------|
| Conductor Material             | Copper                         |
| Connector Finish               | Tin                            |
| Insulation                     | NA                             |
| Material                       | Copper                         |
| Wire Binding Hardware Finish   | Nickel Strick, Zinc, Green Dye |
| Wire Binding Hardware Material | Stainless steel                |

## Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

## Bolt and Screw Sizes

|                                        |     |
|----------------------------------------|-----|
| Mounting Bolt/Stud Size                | #10 |
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Screw Size                | 1/4 |
| Wire Binding Torque                    | 35  |

## General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 50 |
| Direct Burial               | Yes             |
| Dual Rated                  | No              |
| NEMA Code                   | S-573-2         |
| UPC Code                    | 78366996018     |

## Testing Standards

|                          |                                                                                                            |
|--------------------------|------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                   |
| CSA Standard             | C22.2 No. 65-03                                                                                            |
| Prop65 Compliance        | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a> |
| UL Control Number        | 667P                                                                                                       |
| UL / CULUS Specification | UL 2703 Listed                                                                                             |
| UL File Number           | E354420 Vol. 2                                                                                             |

## Conductor Ranges

|                                                        |                 |
|--------------------------------------------------------|-----------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA              |
| Conductor Range AL Stranded (Primary, run, main, line) | NA              |
| Conductor Range AL Stranded (Secondary, tap, load)     | NA              |
| Conductor Range CU Solid (Primary, run, main, line)    | 10 Sol - 14 Sol |
| Conductor Range CU Solid (Secondary, tap, load)        | NA              |
| Conductor Range CU Stranded (Primary, run, main, line) | 4 Str - 14 Str  |
| Conductor Range CU Stranded (Secondary, tap, load)     | NA              |
| Conductor Range AL Solid (Primary, run, main, line)    | NA              |