



SKU: GBL-4SS

UPC: 0783669960075

Features & Benefits:

Description: Aluminum Lay-in Ground Lug, Dual Rated, Conductor Range 4-14, Tin Plated, Stainless steel hardware, UL

Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Mounting Kit Hardware Part #	GBL-MH1
Number of Conductors	1
Number of Mounting Holes	1
Number of Ports / Wireways	1
Wire Orientation	NA

Dimensions

Dimension G (IN)	0.2
Dimension G (mm)	5.08
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.85
Height BX (IN)	2.25
Height (mm)	21.59
Length (IN)	1.1
Length (mm)	27.94
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.218
Mounting Hole Diameter (mm)	5.5372
Tang Length (IN)	0.48
Tang Length (mm)	12.192
Tang Thickness (IN)	0.12
Tang Thickness (mm)	3.048
Tang Width (IN)	0.385
Tang Width (mm)	9.779
Weight (LB)	0.021
Weight BX (LB)	1.95
Width (IN)	0.385
Width BX (IN)	5
Width (mm)	9.779

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA

Material	Aluminum
Wire Binding Hardware Finish	Nickel Strick, Zinc, Green Dye
Wire Binding Hardware Material	Stainless steel

Additional Technical Specifications

Conductor Type	Stranded
-----------------------	----------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	8 AWG = 25

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 50
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-573-2
UPC Code	78366996007

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	667P
UL / CULUS Specification	UL 2703 Listed
UL File Number	E34440

Color

Color	Silver
--------------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	10 Sol - 14 Sol