



SKU: GGA-6

UPC: 0783669260106

Features & Benefits:

Description: Permagraund Copper Grounding Grid, Main Conductor Range 500-250, Tap Range 500-250, Ground Rod Sizes 5/8 to 3/4in, Rebar Sizes #5-#6, UL, CSA

Specs

Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Index Number Main	998
ILSCOs Die Index Number Tap	1011

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	500 kcmil - 250 kcmil
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	3/4
Rebar Size(s) Main	#6 (3/4)

Dimensions

Height (IN)	1.48
Height BX (IN)	4.25
Height (mm)	37.592
Length (IN)	4.765
Length (mm)	121.031
Weight (LB)	1.4614809214246
Width (IN)	4.765
Width BX (IN)	7.75
Width (mm)	121.031

Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type Stranded

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-573-3
UPC Code	78366926010

Bolt and Screw Sizes

Mounting Bolt/Stud Size NA

Testing Standards

CSA File Number	LR-5465
CSA Standard	C22.2 No. 41
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

Environment and Temperature

Temperature Rating NA

Color

Color Copper