



**SKU:** GGC-6

**UPC:** 0783669260601

**Features & Benefits:**

**Description:** Permagraund Copper Grounding Grid, Main Conductor Range 500-250, Tap Range 2/0-1/0, Ground Rod Sizes 5/8 to 3/4in, Rebar Sizes #5-#6, UL, CSA

## Specs

### Additional Class Attributes

Barrel Marking	Hard
Fixing Type	NA
ILSCOs Die Catalog Number	ILD-998
ILSCOs Die Index Number	998

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	2/0 Str - 1/0 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8 to 3/4
Rebar Size(s) Main	#6 (3/4)

### Dimensions

Height (IN)	2.565
Height BX (IN)	2
Height (mm)	65.151
Length (IN)	1.365
Length (mm)	34.671
Weight (LB)	0.452
Width (IN)	0.75
Width BX (IN)	6.1875
Width (mm)	19.05

### Material and Finish

Conductor Material	Copper
Connector Finish	Bare
Insulation	NA
Material	Copper

### **Additional Technical Specifications**

**Conductor Type** Stranded

### **General**

<b>Bag Quantity</b>	1
<b>Carton Quantity Description</b>	STD PACK QTY 20
<b>Direct Burial</b>	Yes
<b>Dual Rated</b>	No
<b>NEMA Code</b>	S-573-3
<b>UPC Code</b>	78366926060

### **Bolt and Screw Sizes**

**Mounting Bolt/Stud Size** NA

### **Testing Standards**

<b>CSA File Number</b>	LR-5465
<b>CSA Standard</b>	C22.2 No. 41
<b>Prop65 Compliance</b>	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
<b>UL Control Number</b>	667P
<b>UL / CULUS Specification</b>	UL 467 Listed
<b>UL File Number</b>	E34440

### **Environment and Temperature**

**Temperature Rating** NA

### **Color**

**Color** Copper