



**SKU:** GPL-4

**UPC:** 0783669262063

**Features & Benefits:**

**Description:** Permagraund Copper U-Bolt Ground Clamp, Conductor Range 4-8 Sol, Pipe Size 3/8in, Ground Rod Sizes 5/8 to 3/4in, Rebar Size #6, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Parallel

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	4 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
Ground Rod Size	5/8
NPS/IPS Pipe Size	3/8
Rebar Size(s) Main	#6 (3/4)

### Dimensions

Drive Size Main	3/8
Drive Type Main	External Hex
Height (IN)	2.875
Height BX (IN)	4.75
Height (mm)	73.025
Length (IN)	2.25
Length (mm)	57.15
Weight (LB)	0.682
Weight BX (LB)	8.444
Width (IN)	1.562
Width BX (IN)	5.25
Width (mm)	39.6748

### Material and Finish

Conductor Material	Copper
Connector Finish	NA

Insulation	NA
Material	Copper
Wire Binding Hardware Material	Silicon bronze

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Clamping Bolt Size	1/4
Number of Wire Binding Screws per Port	0
Wire Binding Screw Size	NA

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	Yes
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366926206

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440