



**SKU:** IKB-350

**UPC:** 0783669480023

**Features & Benefits:**

**Description:** Copper Two-Bolt Split Bolt, Main Conductor Range 350-250, Tap Range 350-10, UL

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1

### Dimensions

Drive Size Main	NA
Drive Type Main	External Hex
Height (IN)	2.575
Height BX (IN)	2.75
Height (mm)	65.405
Length (IN)	2.144
Length (mm)	54.4576
Weight (LB)	0.743
Width (IN)	1.374
Width BX (IN)	6
Width (mm)	34.8996

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	NA

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366948002

### Testing Standards

CSA File Number	NA
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
RUS Listed	Yes
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Copper
-------	--------

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	10 Sol
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	350 kcmil - 10 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

### Voltage

Voltage Rating	35 kV
----------------	-------