



SKU: IKS-350

UPC: 0783669490022

Features & Benefits:

Description: Copper Two-Bolt Split Bolt, Main Conductor Range 350-250, Tap Range 350-6, Tin Plated, UL

Specs

Additional Class Attributes

Connection	Mechanical
Number of Conductors	2
Number of Poles	1

Dimensions

Drive Size Main	NA
Drive Type Main	External Hex
Height (IN)	2.825
Height BX (IN)	2.75
Height (mm)	71.755
Length (IN)	2.144
Length (mm)	54.4576
Weight (LB)	0.104416781163024
Width (IN)	1.374
Width BX (IN)	6
Width (mm)	34.8996

Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Number of Wire Binding Screws per Port	2
Wire Binding Screw Size	NA

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 12
Direct Burial	No
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366949002

Testing Standards

CSA File Number	NA
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	NA
---------------------------	----

Color

Color	Copper
--------------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	350 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	350 kcmil - 6 Str
Conductor Range AL Solid (Primary, run, main, line)	NA