

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 3
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-4
UPC Code	78366953277

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Black
-------	-------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	10 Sol - 12 Sol
Conductor Range AL Stranded (Primary, run, main, line)	500 kcmil - 250 kcmil
Conductor Range AL Stranded (Secondary, tap, load)	10 Str - 12 Str
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 12 Sol
Conductor Range CU Stranded (Primary, run, main, line)	500 kcmil - 250 kcmil
Conductor Range CU Stranded (Secondary, tap, load)	10 Str - 12 Str
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	300 V (480 Grounded Y System)
----------------	-------------------------------

Additional Technical Specifications

Connector Amperage Rating AL (Derated where applicable)	35 Amps
Connector Amperage Rating CU (Derated where applicable)	40 Amps
Conductor Type	Solid